



شهادة مطابقة CERTIFICATE OF CONFORMITY

Certificate Number:	24-11-131534/E24-11-136651/NB0007	رقم الشهادة:
Registration Date:	25/11/2024	تاريخ التسجيل:
Valid Until:	24/11/2027	صالحة لغاية:
Issued To:	Emerson FZE P.O. Box 17034 ,Freezone South Jebel Ali Dubai ,United Arab Emirates	أصدرت إلى:
Sector:	Electrical	قطاع: كهرباء
Product Category:	ECAS-Ex	تصنيف المنتج: الأجهزة الكهربائية المعدة للاستخدام في الأجواء القابلة للانفجار
Product Sub-Category:	ECAS-Ex	التصنيف الفرعي للمنتج: الأجهزة الكهربائية المعدة للاستخدام في الأجواء القابلة للانفجار

Please check Schedule of certification for all product details يرجى التحقق من بيان التسجيل المرفق لجميع تفاصيل المنتجات

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology



Products are registered under the Emirates Conformity Assessment Scheme (ECAS) based on compliance to the Approved Standards

المنتجات مسجلة في نظام تقويم المطابقة الإماراتي (إيكاس) بناء على مطابقتها للمواصفات المعتمدة

600565554

www.moiat.gov.ae

[@MoIAT](#)



تم اصدار هذا المستند الكترونيا ولا يحتاج إلى ختم أو توقيع.
This document has been issued electronically and doesn't require a stamp and signature.



بيان التسجيل SCHEDULE OF CERTIFICATION Ministry of Industry and Advanced Technology

Company Name:	Emerson FZE	اسم الشركة:
Product Category:	ECAS-Ex	الأجهزة الكهربائية المعدة للاستخدام في الأجواء القابلة للانفجار تصنيف المنتج:
Certificate No.:	24-11-131534/E24-11-136651/NB0007	رقم التسجيل:
Registration Date:	25/11/2024	تاريخ التسجيل:
Valid Until:	24/11/2027	صالح لغاية:

Sr.No.	الاسم التجاري Brand Name	رقم الموديل Model Number	تفاصيل المنتج Product Details	تصنيف النجوم Star Rating	الأبعاد/الحجم Dimension/ Size	التقارير Reports	المواصفات المطبقة Applicable Standards	بلد المنشأ Country Of Origin
1	Topworx	Series 7 Proximity Switches	Proximity Switches; Type of Protection: Ex d, Ex tD; Marking: Ex db IIC T6* Gb T6 (-40°C ≤ Ta ≤ +50°C)*, Ex tb IIIC T85°C* Db (-40°C ≤ Ta ≤ +50°C)* IP66; For *, please refer IECEx BAS 08.0122X Issue No: 9	N/A	N/A	IECEX BAS 08.0122X GB/BAS/ExTR08.0252/00 GB/BAS/ExTR09.0023/00 GB/BAS/ExTR09.0108/00 GB/BAS/ExTR10.0037/00 GB/BAS/ExTR12.0153/00 GB/BAS/ExTR13.0078/00 GB/BAS/ExTR13.0211/00 GB/BAS/ExTR15.0150/00 GB/BAS/ExTR21.0096/00 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-0, UAE.S IEC 60079-1, UAE.S IEC 60079-31	United States

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology





بيان التسجيل
SCHEDULE OF CERTIFICATION
Ministry of Industry and Advanced Technology

2	Topworx	Series 7 Proximity Switches	Proximity Switches; Type of Protection: Intrinsic Safety; Marking: Ex ia IIC T6/T4/T3 Ga, Ex ia IIIC T-200 85°C / T- 200 135°C / T-200 200°C Da; For more details, please refer IECEX BAS 09.0080X Issue No: 10	N/A	N/A	IECEX BAS 09.0080X GB/BAS/ExTR09.0113/00 GB/BAS/ExTR10.0128/00 GB/BAS/ExTR11.0100/00 GB/BAS/ExTR12.0098/00 GB/BAS/ExTR12.0197/00 GB/BAS/ExTR15.0188/00 GB/BAS/ExTR17.0174/00 GB/BAS/ExTR19.0031/00 GB/BAS/ExTR20.0115/00 GB/BAS/ExTR22.0193/00 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-11, UAE.S IEC 60079-0	United States
3	Topworx	70 Series Connection Head	Connection Head; Type of Protection: Flameproof, Increased Safety, Dust, Protection by Enclosure; Marking: Ex db eb IIC T6 (-40°C ≤ Ta ≤ +50°C) Gb or T4 (-40°C ≤ Ta ≤ +100°C), Ex tb IIIC T85°C (-40°C ≤ Ta ≤ +50°C) Db IP66 or T130°C (-40°C ≤ Ta ≤ +100°C)	N/A	N/A	GB/BAS/ExTR21.0096/00 IECEX BAS 09.0135X GB/BAS/ExTR09.0191/00 GB/BAS/ExTR11.0222/00 GB/BAS/ExTR11.0308/00 GB/BAS/ExTR12.0301/00 GB/BAS/ExTR19.0057/00 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-0, UAE.S IEC 60079-1, UAE.S IEC 60079-7, UAE.S IEC 60079-31	United States

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology



بيان التسجيل
SCHEDULE OF CERTIFICATION
Ministry of Industry and Advanced Technology

4	Topworx	70 Series Micro Switch	Micro Switch; Type of Protection: Flameproof and flameproof/increased safety and dust protection by enclosure; Marking: Ex db IIC T6 Gb (Tamb -40°C to +75°C) or Ex db eb IIC T6 Gb (Tamb -40°C to +75°C) and Ex tb IIIC T85°C Db IP66/68; For more details, please refer IECEx BAS 13.0086X Issue No: 6	N/A	N/A	GB/BAS/ExTR21.0096/00 IECEX BAS 13.0086X GB/BAS/ExTR13.0187/00 GB/BAS/ExTR15.0076/00 GB/BAS/ExTR18.0098/00 GB/BAS/ExTR21.0042/00 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-0, UAE.S IEC 60079-1, UAE.S IEC 60079-7, UAE.S IEC 60079-31	United States
5	Topworx	70 Series Micro Junction	Micro Junction; Type of Protection: Intrinsic Safety; Marking: Ex ia IIC T6/T4/T3 Ga, Ex ia IIIC T-200 85°C/T-200 135°C/T-200 200°C Da; For more details, please refer IECEx BAS 15.0136X Issue No: 3	N/A	N/A	GB/BAS/ExTR21.0042/00 IECEX BAS 15.0136X GB/BAS/ExTR15.0298/00 GB/SGS/ExTR24.0017/00 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-11, UAE.S IEC 60079-0	United States

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology





بيان التسجيل
SCHEDULE OF CERTIFICATION
Ministry of Industry and Advanced Technology

6	Topworx	TXP	Mechanical Switch; Type of Protection: Flameproof "db" and Dust "tb"; Marking: Limit Switch Enclosure - without solenoid - Ex db IIC T6/T5/T4 Gb, Ta = -65°C to +40°C/+60°C/+80°C, Ex tb IIIC T85°C/T100°C/T135°C Db, Ta = -50°C to +40°C/+60°C/+80°C; Solenoid Switch - with solenoid - Ex db IIB T6/T5/T4 Gb, Ta = -65°C to +40°C/+60°C/+80°C, Ex tb IIIC T85°C/T100°C/T135°C Db, Ta = -50°C to +40°C/+60°C/+80°C	N/A	N/A	IECEX SIR 06.0054X GB/SIR/ExTR06.0196/00 GB/SIR/ExTR09.0146/00 GB/SIR/ExTR11.0263/00 GB/SIR/ExTR11.0298/00 GB/SIR/ExTR12.0117/00 GB/SIR/ExTR13.0061/00 GB/SIR/ExTR13.0334/00 GB/SIR/ExTR17.0052/00 GB/SIR/ExTR17.0171/00 GB/SIR/ExTR18.0237/00 GB/SIR/ExTR19.0053/00 GB/SIR/ExTR20.0136/00 GB/SIR/ExTR21.0088/00 GB/SIR/ExTR24.0024/00 GB/SIR/ExTR24.0102/00 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-0, UAE.S IEC 60079-1, UAE.S IEC 60079-31	United States
---	---------	-----	--	-----	-----	---	--	---------------

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology





بيان التسجيل
SCHEDULE OF CERTIFICATION
Ministry of Industry and Advanced Technology

7	Topworx	TXS	Mechanical Switch; Type of Protection: Flameproof "db" and Dust "tb"; Marking: Limit Switch Enclosure - without solenoid - Ex db IIC T6/T5/T4 Gb, Ta = -65°C to +40°C/+60°C/+80°C, Ex tb IIIC T85°C/T100°C/T135°C Db, Ta = -50°C to +40°C/+60°C/+80°C; Solenoid Switch - with solenoid - Ex db IIB T6/T5/T4 Gb, Ta = -65°C to +40°C/+60°C/+80°C, Ex tb IIIC T85°C/T100°C/T135°C Db, Ta = -50°C to +40°C/+60°C/+80°C	N/A	N/A	IECEX SIR 06.0054X GB/SIR/ExTR06.0196/00 GB/SIR/ExTR09.0146/00 GB/SIR/ExTR11.0263/00 GB/SIR/ExTR11.0298/00 GB/SIR/ExTR12.0117/00 GB/SIR/ExTR13.0061/00 GB/SIR/ExTR13.0334/00 GB/SIR/ExTR17.0052/00 GB/SIR/ExTR17.0171/00 GB/SIR/ExTR18.0237/00 GB/SIR/ExTR19.0053/00 GB/SIR/ExTR20.0136/00 GB/SIR/ExTR21.0088/00 GB/SIR/ExTR24.0024/00 GB/SIR/ExTR24.0102/00 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-0, UAE.S IEC 60079-1, UAE.S IEC 60079-31	United States
---	---------	-----	--	-----	-----	---	--	---------------

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology





بيان التسجيل
SCHEDULE OF CERTIFICATION
Ministry of Industry and Advanced Technology

8	Topworx	DXP	Switchboxes; Type of Protection: Flameproof db and Dust tb; For markings, please refer IECEx SIR 07.0093X Issue No: 20	N/A	N/A	GB/SIR/ExTR11.0263/00 GB/SIR/ExTR11.0298/00 GB/SIR/ExTR13.0334/00 GB/SIR/ExTR19.0053/00 GB/SIR/ExTR21.0088/00 GB/SIR/ExTR24.0024/00 GB/SIR/ExTR24.0102/00 IECEX SIR 07.0093X GB/CSAE/ExTR21.0022/00 GB/SIR/ExTR08.0031/00 GB/SIR/ExTR09.0066/00 GB/SIR/ExTR12.0194/00 GB/SIR/ExTR12.0234/00 GB/SIR/ExTR12.0317/00 GB/SIR/ExTR12.0318/00 GB/SIR/ExTR14.0112/00 GB/SIR/ExTR18.0097/00 GB/SIR/ExTR20.0142/00 GB/SIR/ExTR20.0214/00 GB/SIR/ExTR23.0052/00 GB/SIR/ExTR23.0125/00 GB/SIR/ExTR24.0102/01 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-0, UAE.S IEC 60079-1, UAE.S IEC 60079-31	United States
---	---------	-----	--	-----	-----	--	--	---------------

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology





بيان التسجيل
SCHEDULE OF CERTIFICATION
Ministry of Industry and Advanced Technology

9	Topworx	DXS	Switchboxes; Type of Protection: Flameproof db and Dust tb; For markings, please refer IECEx SIR 07.0093X Issue No: 20	N/A	N/A	GB/SIR/ExTR11.0263/00 GB/SIR/ExTR11.0298/00 GB/SIR/ExTR13.0334/00 GB/SIR/ExTR19.0053/00 GB/SIR/ExTR21.0088/00 GB/SIR/ExTR24.0024/00 GB/SIR/ExTR24.0102/00 IECEx SIR 07.0093X GB/CSAE/ExTR21.0022/00 GB/SIR/ExTR08.0031/00 GB/SIR/ExTR09.0066/00 GB/SIR/ExTR12.0194/00 GB/SIR/ExTR12.0234/00 GB/SIR/ExTR12.0317/00 GB/SIR/ExTR12.0318/00 GB/SIR/ExTR14.0112/00 GB/SIR/ExTR18.0097/00 GB/SIR/ExTR20.0142/00 GB/SIR/ExTR20.0214/00 GB/SIR/ExTR23.0052/00 GB/SIR/ExTR23.0125/00 GB/SIR/ExTR24.0102/01 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-0, UAE.S IEC 60079-1, UAE.S IEC 60079-31	United States
---	---------	-----	--	-----	-----	--	--	---------------

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology



بيان التسجيل SCHEDULE OF CERTIFICATION

Ministry of Industry and Advanced Technology

10	Topworx	TX*	Valve Position Indicators; Type of Protection: Intrinsic Safety ia and Dust Protection by Enclosure tb; Marking: Ex ia IIC T* Gb (Ta = - [°] C to + [°] C), Ex tb III C T [°] C Db (Ta = - [°] C to + [°] C), IP66/67; For *, please refer IECEx SIR 14.0045X Issue No: 10	N/A	N/A	IECEX SIR 14.0045X GB/SIR/ExTR14.0192/00 GB/SIR/ExTR15.0260/00 GB/SIR/ExTR16.0281/00 GB/SIR/ExTR19.0053/00 GB/SIR/ExTR19.0073/00 GB/SIR/ExTR20.0142/00 GB/SIR/ExTR20.0154/00 GB/SIR/ExTR21.0088/00 GB/SIR/ExTR22.0140/00 GB/SIR/ExTR24.0005/00 GB/SIR/ExTR24.0040/00 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-11, UAE.S IEC 60079-0, UAE.S IEC 60079-31	United States
11	Topworx	D-Series	Switchbox; Type of Protection: Intrinsic Safety ia and Dust Protection by Enclosure tb; Marking: Ex ia IIC T4 Gb or Ex ia IIC T5 Gb or Ex ia IIC T6 Gb Ex tb IIIC T [°] C Db; Ta = - [°] C to + [°] C; For *, please refer IECEx SIR 14.0078X Issue No: 10	N/A	N/A	IECEX SIR 14.0078X GB/CSAE/ExTR21.0022/00 GB/SIR/ExTR15.0178/00 GB/SIR/ExTR17.0150/00 GB/SIR/ExTR18.0194/00 GB/SIR/ExTR19.0053/00 GB/SIR/ExTR20.0142/00 GB/SIR/ExTR20.0155/00 GB/SIR/ExTR20.0214/00 GB/SIR/ExTR21.0088/00 GB/SIR/ExTR22.0134/00 GB/SIR/ExTR24.0006/00 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-11, UAE.S IEC 60079-0, UAE.S IEC 60079-31	United States

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology





بيان التسجيل
SCHEDULE OF CERTIFICATION
Ministry of Industry and Advanced Technology

12	Topworx	DX*- S*C*****	D2 HART7 PST ESD Switchbox; Type of Protection: Flameproof "db", Non-sparking "nA", Hermetically-sealed "nC"; Dust Ignition Protection by Enclosure "tb" and "tc"; Marking: Ex db IIC T6...T4 Gb, Ex db IIB + H2 T6...T4 Gb, Ex tb IIIC T85°C...T135°C Db, Ex tc IIIC T135°C Dc, Ex nA nC IIC T4 Gc, -40°C to +60°C, -40°C to +80°C	N/A	N/A	IECEX UL 19.0090X US/UL/ExTR19.0102/00 US/UL/ExTR19.0102/01 US/UL/ExTR19.0102/02 US/UL/ExTR19.0102/03 US/UL/ExTR19.0102/04 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-0, UAE.S IEC 60079-1, UAE.S IEC 60079-15, UAE.S IEC 60079-31	United States
----	---------	------------------	---	-----	-----	---	---	---------------

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology





بيان التسجيل
SCHEDULE OF CERTIFICATION
Ministry of Industry and Advanced Technology

13	Topworx	DX*- S*1*****	D2 HART7 PST ESD Switchbox; Type of Protection: Flameproof "db", Non-sparking "nA", Hermetically-sealed "nC"; Dust Ignition Protection by Enclosure "tb" and "tc"; Marking: Ex db IIC T6...T4 Gb, Ex db IIB + H2 T6...T4 Gb, Ex tb IIIC T85°C...T135°C Db, Ex tc IIIC T135°C Dc, Ex nA nC IIC T4 Gc, -40°C to +60°C, -40°C to +80°C	N/A	N/A	IECEX UL 19.0090X US/UL/ExTR19.0102/00 US/UL/ExTR19.0102/01 US/UL/ExTR19.0102/02 US/UL/ExTR19.0102/03 US/UL/ExTR19.0102/04 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-0, UAE.S IEC 60079-1, UAE.S IEC 60079-15, UAE.S IEC 60079-31	United States
----	---------	------------------	---	-----	-----	---	---	---------------

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology





بيان التسجيل SCHEDULE OF CERTIFICATION

Ministry of Industry and Advanced Technology

14	Topworx	DX*- S*2*****	D2 HART7 PST ESD Switchbox; Type of Protection: Flameproof "db", Non-sparking "nA", Hermetically-sealed "nC"; Dust Ignition Protection by Enclosure "tb" and "tc"; Marking: Ex db IIC T6...T4 Gb, Ex db IIB + H2 T6...T4 Gb, Ex tb IIIC T85°C...T135°C Db, Ex tc IIIC T135°C Dc, Ex nA nC IIC T4 Gc, -40°C to +60°C, -40°C to +80°C	N/A	N/A	IECEX UL 19.0090X US/UL/ExTR19.0102/00 US/UL/ExTR19.0102/01 US/UL/ExTR19.0102/02 US/UL/ExTR19.0102/03 US/UL/ExTR19.0102/04 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-0, UAE.S IEC 60079-1, UAE.S IEC 60079-15, UAE.S IEC 60079-31	United States	
15	Topworx	DX*- S*0***S*****	D2 HART7 PST ESD Switchbox; Type of Protection: Intrinsic Safety "ia"; Marking: Ex ia IIC T4 Ga, Ex ia IIIC T135°C Db, -40°C to +80°C	N/A	N/A	IECEX UL 20.0070X US/UL/ExTR20.0072/00 US/UL/ExTR20.0072/01 US/UL/ExTR20.0072/02 US/UL/ExTR20.0072/03 US/UL/ExTR20.0072/04 US/UL/ExTR20.0072/05 GB/SIR/QAR07.0025/12	UAE.S IEC 60079-11, UAE.S IEC 60079-0	United States	
Nothing Follows									

intertek
Total Quality. Assured.

جهة معينة من قبل وزارة الصناعة والتكنولوجيا المتقدمة
Notified body by Ministry of Industry and Advanced Technology

