

# PACSystems™ IPC 2010

Compact Industrial PC

Emerson's PACSystems IPC 2010 Industrial PC (IPC) delivers high-efficiency computing performance and graphics capabilities in our most compact, ruggedized package. Like other award winning products in the PACSystems IPC product line, the IPC 2010 offers customers high reliability and a long deployment life thanks to fanless cooling and soldered memory.

The IPC 2010 computing platform, which includes industrial-grade microprocessor, memory and operating system paired with pre-loaded, pre-licensed edge software, enables customized data collection and aggregation, data protocol conversion, and basic analytics applications for real-time optimization and visualization of operations.

This high-efficiency IPC is well suited to processing time-series data from various sources like PLC's, cameras, sensors, flow meters or valve manifolds, powering analytical solutions for remote monitoring, leak detection, and preventative maintenance applications.

The IPC 2010 comes with everything you need to start creating ROI out-of-the box. An IIoT-ready Linux operating system and PACEdge application enablement platform come pre-installed from the factory. In addition, there are options to add pre-loaded and pre-licensed Movicon® Connex and Movicon WebHMI software, enabling additional functionality and benefits as detailed in the following table.



## Software Options and Benefits

Product Name	Functionality and Benefits
<b>PACEdge</b>	An application enablement platform for the development of scalable data intensive Industry 4.0 solutions. It provides integration between OT and IT domains without disrupting OT assets, architectures or systems while satisfying IT cybersecurity, communications and application requirements. PACEdge is capable of supporting integrations and architectures ranging from IIoT gateways and remote monitoring to edge AI/ML analytics and data visualization. The PACEdge software environment provides all the tools necessary to collect, store, process, share, visualize, secure and integrate data allowing users to focus on applications and solutions instead of tools and platforms
<b>PACEdge with Movicon Connex</b>	A gateway communications center for Machine to Machine, Cloud and IIoT connectivity systems that facilitates data collection, analysis, and reporting. Connex quickly and intuitively links a multitude of devices for better data flow. With its built-in protocol libraries, Connex can collect and publish data to the cloud, manage information flows to business systems, or connect field devices to software applications or to each other effortlessly and safely.
<b>PACEdge with Movicon Connex and WebHMI</b>	A comprehensive solution for delivering visualization and data collection that also maintains a seamless, intuitive experience. Whether users are accessing critical data directly in the plant, collecting information via a workstation in a control room, or checking system performance via mobile device from outside the facility, powerful visualization tools ensure a consistent display for fast delivery and interpretation of critical data

For more information:  
[www.Emerson.com/PACSystems](http://www.Emerson.com/PACSystems)

**PACSYSTEMS™**



## Specifications

### Technical Specifications

Item	Specification
Processor	ARM Cortex-A53 CPU (2 Cores at 1.2 GHz)
Memory	2 GB DDR4-1600
Ethernet	Two 10/100/1000BASE-T Ethernet ports
Graphics Interface	One DisplayPort via USB-C connector (with integrated cable retention) Part Number YLB-UIPC-01-1
USB Interface	Two USB 2.0
Serial Communications	One RS-232
Internal Storage	eMMC 64 GB
Removeable Storage	One Micro SD Card Slot (SDXC type supported)

### Dimension and Weight

Item	Specification
Dimensions	120 x 45 x 101 mm
Weight	340 g

### Mounting

Integrated DIN Rail
---------------------

### Power

Item	Specification
Input	10 V – 30 V DC
Backup	CR2032 lithium coin battery

### Environmental

Thermal performance is highly dependent on end application workload, pre-configured processor TDP value, installed expansion cards, IPC mounting orientation etc., Please consult User Manual for details and recommendations.	Range	Operating	Storage
	Standard	-20 °C up to +70 °C	-40°C up to +85 °C
	Humidity	5-95% @ +40 °C	5-95% @ +40 °C
	Altitude	6,600 ft. (2.0 km)	40000 ft. (12 km)

### Software Support

<b>Ubuntu Desktop 20.04.05 LTS</b>
PACEdge v2.3.0 (based on Ubuntu 20.04 Server)
PACEdge with Optional Movicon Connex (pre-loaded options available)
PACEdge with Optional Movicon Connex & WebHMI (pre-loaded options available)

## EMC and Safety

Item	Specification
EMC	<p>EMC Directive 2014/30/EU</p> <p>EN 61000-6-4 Emission standard for industrial environments</p> <p>EN 61000-6-2 Immunity standard for industrial environments</p> <p>FCC Part 15 B</p> <p>This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p> <p>CAN ICES-3 (A)/NMB-3(A)</p>
Product Safety	<p>LVD Directive 2014/35/EU: EN/IEC 62368-1</p> <p>UL 62368-1 -1</p>

## Ordering Information

Part Number	Product	Product Description
UIPCA21E2HE0A	PACSystems IPC 2010 w/ PACEdge	An industrial PC with an ARM Cortex-A53 dual-core 1.2 GHz processor, 2 GB RAM, 64 G SSD, -20 °C to 70 °C operating temperature range, integral DIN rail mounting, Linux operating system and pre-loaded, pre-licensed PACEdge software.
UIPCA21E2HC0A	PACSystems IPC 2010 w/ PACEdge and Movicon Connex	An industrial PC with an ARM Cortex-A53 dual-core 1.2 GHz processor, 2 GB RAM, 64 G SSD, -20 °C to 70 °C operating temperature range, integral DIN rail mounting, Linux operating system and pre-loaded, pre-licensed PACEdge software. Includes a pre-loaded Movicon Connex software license with the Automation Driver Pack, Basic Driver Pack and 2000 OPC UA Tags.
UIPCA21E2HW0A	PACSystems IPC 2010 w/ PACEdge, Movicon Connex and Movicon WebHMI	An industrial PC with an ARM Cortex-A53 dual-core 1.2 GHz processor, 2 GB RAM, 64 G SSD, -20 °C to 70 °C operating temperature range, integral DIN rail mounting, Linux operating system and pre-loaded, pre-licensed PACEdge software. Includes a pre-loaded Movicon Connex software license with the Automation Driver Pack, Basic Driver Pack, 2000 OPC UA Tags and Movicon WebHMI
YLB-UIPC-01-1	PACSystems USB-C to DisplayPort Cable	For graphics interface with PACSystem IPC 2010 Industrial PC

## Wi-Fi / Cellular Kits

Part Number	Product	Product Description
UIPC-WMC-4G-GB	PACSystems IPC 2010 Wi-Fi / Cellular Kit - Global	Global Communications Version (4G – GSM+LTE & Wi-Fi), Router RUT241, 4-Pin Power Adapter with I/O Access, 2x Mobile antennas (swivel, SMA male) 1x Wi-Fi antenna (swivel, RP-SMA male), Ethernet cable (0.25 m), SIM Card Kit, IPC 2010 Mounting Clip, Quick Start Guide.
UIPC-WMC-4G-NA	PACSystems IPC 2010 Wi-Fi / Cellular Kit – North America	North American Communications Version (4G -GSM+LTE & Wi-Fi), Router RUT241, 4-Pin Power Adapter with I/O Access, 2x Mobile antennas (swivel, SMA male) 1x Wi-Fi antenna (swivel, RP-SMA male), Ethernet cable (0.25 m), SIM Card Kit, IPC 2010 Mounting Clip, Quick Start Guide.