

AMS 2140 Machinery Health Analyzer

Break-Away Cable Improves Safety and Prevents Accidents

Personal safety is important in every plant!

Promote safety in the workplace by installing break-away safety cables on your AMS 2140 Machinery Health Analyzers. Safety connectors greatly reduce the likelihood of technicians and equipment being pulled into rotating machinery during route-based vibration monitoring. The cables are designed to withstand the harshest industrial environments.



Technical Specifications

Performance	English	SI
Cable Style	Multi Conductor - Shielded	Multi Conductor - Shielded
Number of Conductors	2	2
Connector Model (sensor side)	extended strain relief	extended strain relief
Connector Style (sensor side)	MIL-C-5015	MIL-C-5015
Connection Type (sensor side)	2-socket	2-socket
Coupling Method (sensor side)	Threaded	Threaded
Connector Model (termination)	3-pin half-breakaway	3-pin half-breakaway
Coupling Method (termination)	Breakaway	Breakaway
Environmental		
Temperature Range	-22 to 176°F	-30 to 80°C
Electrical		
Capacitance	31 pF/ft	102 pF/m

Technical Specifications

Physical	English	SI
Cable Jacket Diameter ($\pm .010$ in)	0.21 in	5.33 mm
Cable Jacket Material	TPE	TPE
Cable Jacket Color	Black	Black
Conductor Style	Stranded - 21 Strands 36 AWG	Stranded - 21 Strands 36 AWG
Conductor Material	Tin Plated Copper	Tin Plated Copper
Conductor Diameter (23 AWG)	0.028 in	0.028 in
Insulation Material Over Conductor(s)	Polypropylene	Polypropylene
Shield Type Over Conductor(s)	Braid: 90% Minimum Coverage	Braid: 90% Minimum Coverage
Shield Material Over Conductor(s)	Tinned Copper	Tinned Copper
Bend Radius	2.1 in	53.3 mm
Weight	0.25 lb	0.11 kg
Size - Length	6 ft	1.829 m
Temperature Range	-22 to 176°F	-30 to 80°C

All specifications are at room temperature unless otherwise specified.

Performance	English	SI
Cable Style	Multi Conductor - Shielded	Multi Conductor - Shielded
Number of Conductors	2	2
Connector Model	Half Breakaway	Half Breakaway
Connection Type	3-socket	3-socket
Coupling Method	Breakaway	Breakaway
Connector Model (termination)	5-pin Turck	5-pin Turck
Coupling Method	Threaded	Threaded
Environmental		
Temperature Range	-58 to 250°F	-50 to 121°C
Electrical		
Capacitance	36 pF/ft	6.35 mm
Performance	English	SI
Cable Jacket Diameter	0.25 in	6.35 mm
Cable Jacket Material	Polyurethane	Polyurethane
Cable Jacket Color	Black	Black
Conductor Style	Stranded - 19 strands 32 AWG	Stranded - 19 strands 32 AWG
Conductor Material	Tin Plated Copper	Tin Plated Copper

Technical Specifications

Physical	English	SI
Conductor Diameter (20 AWG)	0.04 in	1.02 mm
Shield Type Over Bundle	Braid: 90% Minimum Coverage	Braid: 90% Minimum Coverage
Shield Material Over Bundle	Tin Plated Copper	Tin Plated Copper
Bend Radius (minimum)	2.5 in	63.5 mm
Weight	0.67 oz/ft	61.85 gm/m
Size - Length	1 ft	0.304 m

All specifications are at room temperature unless otherwise specified.

Ordering Information

To request a quote or for ordering information, contact your local Emerson representative or send an email to mhm.accessory@emerson.com.

Emerson
Reliability Solutions
 835 Innovation Drive
 Knoxville, TN 37932 USA
 ☎ +1 865 675 2400

🌐 www.emerson.com/ams

©2017, Emerson. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. All other marks are the property of their respective owners.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.