

## **Portable Handheld Shaker**

Emerson's A0340SH Portable Handheld Shaker can be used to verify the output of accelerometers, velocity, and displacement sensors and confirm the entire measurement chain (sensor, cabling, and monitoring system). Battery-powered operation allows testing of online sensors in the field.

| Dynamic Performance                   |                               |
|---------------------------------------|-------------------------------|
| Frequency Output                      | 159.2 Hz (9,552 cpm)          |
| Acceleration (rms switchable to peak) | 1 g rms ±3% (9.81 m/s²)       |
| Velocity                              | 9.81 mm/s rms ±3% (0.39 in/s) |
| Displacement                          | 9.81 μm rms ±3% (0.39 mils)   |
| Transverse Amplitude                  | ≤3%                           |
| Distortion (0 to 20 gram load)        | <7% (hand tightened)          |
| Environmental                         |                               |
| Temperature Range                     | -10 to 55°C (15 to 130°F)     |
| Electrical                            |                               |
| Ramp-Up Time                          | ≤3 seconds                    |
| Battery Power                         | (4) AA batteries (included)   |
| Battery Life/Cycles (250 gram load)   | 2.3 hours / 90 Cycles         |
| External Power (optional)             | 10 Volts (2.4 A)              |
| Automatic Switch Off                  | 1 to 2.5 minutes              |
| Mechanical                            |                               |
| Weight                                | 900 g (31 oz)                 |
| Sensor Mount                          | 1/4 -28UNF-2B                 |
| Mounting Torque (Hand Tighten)        | 1.12 Nm (0.83 lb ft)          |









**A0340SH** August 2017

| Included Accessories  |  |
|---|--|
| Carrying Case   |  |
| Storage Box   |  |
| Battery Pack with (4) AA batteries                                    |  |
| Calibration Mass (For sensors weighting less than 75 grams (2.64 oz)) |  |
| (2) 1/4 -28UNF to 1/4 28 UNF Studs                                    |  |
| 10-32 to 1/4 28 UNF Stud  |  |
| M6x1 to 1/4 28 UNF Stud   |  |

Emerson Reliability Solutions 835 Innovation Drive Knoxville, TN 37932 USA \$\infty\$ +1 865 675 2400

• www.emerson.com/ams

©2017, Emerson. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. All other marks are the property of their respective owners.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.



